

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : OKS 2101

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Anticorrosion additive

Recommended restrictions on use : Restricted to professional users.

### 1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH  
Ganghoferstr. 47  
D-82216 Maisach-Gernlinden  
Tel.: +49 8142 3051 500  
Fax.: +49 8142 3051 599  
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com

National contact :

### 1.4 Emergency telephone number

Emergency telephone number : +49 8142 3051 517  
Warszawa: +48 22 619 66 54

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.  
H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system H336: May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

Long-term (chronic) aquatic hazard, Category 2

H411: Toxic to aquatic life with long lasting effects.

## 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

: Danger

Hazard statements

: H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P273 Avoid release to the environment.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
**Storage:**  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Hazardous components which must be listed on the label:

pentane

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

Hydrocarbons, C6, isoalkanes, <5% n-hexane

### Additional Labelling

EUH208 Contains calcium bis(dinonylnaphthalenesulphonate). May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Active substance with propellant  
Solvent

#### Components

Chemical name	CAS-No. EC-No.  Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
pentane	109-66-0 203-692-4  601-006-00-1 01-2119459286-30-XXXX	Flam. Liq.2; H225 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		>= 10 - < 20
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	265-150-3	Flam. Liq.3; H226 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2;	Note P	>= 2,5 - < 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version 2.6      Revision Date: 07.03.2024      Date of last issue: 07.03.2024      Print Date: 07.03.2024  
Date of first issue: 22.06.2016

	01-2119463258-33	H411; EUH066		
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	918-167-1  01-2119472146-39-XXXX	Flam. Liq.3; H226 Asp. Tox.1; H304; EUH066	Note P	$\geq 1 - < 10$
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9  01-2119484651-34-XXXX	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		$\geq 2,5 - < 10$
isobutane	75-28-5 200-857-2  601-004-00-0 01-2119485395-27-XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	$\geq 1 - < 10$
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	926-605-8  01-2119486291-36-XXXX	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		$\geq 2,5 - < 10$
2-butoxyethanol	111-76-2 203-905-0  603-014-00-0 01-2119475108-36-XXXX	Acute Tox.4; H302 Acute Tox.3; H331 Skin Irrit.2; H315 Eye Irrit.2; H319	ATE (Oral): 1.200 mg/kg; ATE (Inhalation): 3 mg/l;	$\geq 1 - < 10$
calcium bis(dinonylnaphthalen esulphonate)	57855-77-3 260-991-2	Skin Irrit.2; H315 Eye Irrit.2; H319 Skin Sens.1; H317		$\geq 0,1 - < 1$
Substances with a workplace exposure limit :				
butane	106-97-8 203-448-7	Flam. Gas1A; H220		$\geq 30 - < 50$

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version 2.6      Revision Date: 07.03.2024      Date of last issue: 07.03.2024      Print Date: 07.03.2024  
Date of first issue: 22.06.2016

	601-004-00-0 01-2119474691-32-XXXX	Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	
propane	74-98-6 200-827-9  601-003-00-5 01-2119486944-21-XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1)	$\geq 10 - < 20$
Paraffin waxes and Hydrocarbon waxes	8002-74-2 232-315-6	Not classified		$\geq 1 - < 10$

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- If inhaled : Call a physician or poison control centre immediately.  
Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash off immediately with soap and plenty of water.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.  
If accidentally swallowed obtain immediate medical attention.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Rinse mouth with water.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

Aspiration hazard if swallowed - can enter lungs and cause damage.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.

Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness

Drowsiness

Headache

Nausea

Tiredness

Skin contact may provoke the following symptoms:

Erythema

Risks : Central nervous system depression  
Risk of product entering the lungs on vomiting after ingestion.  
Health injuries may be delayed.  
Causes skin irritation.  
May cause an allergic skin reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Fire Hazard  
Do not let product enter drains.  
Contains gas under pressure; may explode if heated.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

for firefighters Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Cool containers/tanks with water spray.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Do not breathe vapours or spray mist.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Refer to protective measures listed in sections 7 and 8.  
Only qualified personnel equipped with suitable protective equipment may intervene.

### 6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.  
Non-sparking tools should be used.

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.  
Do not breathe vapours or spray mist.  
In case of insufficient ventilation, wear suitable respiratory equipment.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

Avoid contact with skin and eyes.  
For personal protection see section 8.  
Keep away from fire, sparks and heated surfaces.  
Smoking, eating and drinking should be prohibited in the application area.  
Wash hands and face before breaks and immediately after handling the product.  
Do not get in eyes or mouth or on skin.  
Do not get on skin or clothing.  
Do not ingest.  
Do not use sparking tools.  
These safety instructions also apply to empty packaging which may still contain product residues.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

### 7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butane	106-97-8	NDSMaximal Admissible Concentration	1.900 mg/m <sup>3</sup>	PL OEL (2018-07-07)
		NDSchMaximal Admissible Temporary Concentration	3.000 mg/m <sup>3</sup>	PL OEL (2018-07-07)
pentane	109-66-0	TWALimit Value - eight hours	1.000 ppm 3.000 mg/m <sup>3</sup>	2006/15/EC (2006-02-09)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version 2.6      Revision Date: 07.03.2024      Date of last issue: 07.03.2024      Print Date: 07.03.2024  
Date of first issue: 22.06.2016

		Further information: Indicative		
		NDSMaximal Admissible Concentration	3.000 mg/m <sup>3</sup>	PL OEL (2018-07-07)
propane	74-98-6	NDSMaximal Admissible Concentration	1.800 mg/m <sup>3</sup>	PL OEL (2018-07-07)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned	NDSMaximal Admissible Concentration	300 mg/m <sup>3</sup>	PL OEL (2018-07-07)
		NDSchMaximal Admissible Temporary Concentration	900 mg/m <sup>3</sup>	PL OEL (2018-07-07)
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	Not Assigned	NDSMaximal Admissible Concentration	500 mg/m <sup>3</sup>	PL OEL (2018-07-07)
		NDSchMaximal Admissible Temporary Concentration	1.500 mg/m <sup>3</sup>	PL OEL (2018-07-07)
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Not Assigned	NDSMaximal Admissible Concentration	500 mg/m <sup>3</sup>	PL OEL (2018-07-07)
		NDSchMaximal Admissible Temporary Concentration	1.500 mg/m <sup>3</sup>	PL OEL (2018-07-07)
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	Not Assigned	NDSMaximal Admissible Concentration	500 mg/m <sup>3</sup>	PL OEL (2018-07-07)
		NDSchMaximal Admissible Temporary Concentration	1.500 mg/m <sup>3</sup>	PL OEL (2018-07-07)
Paraffin waxes and Hydrocarbon waxes	8002-74-2	NDSMaximal Admissible Concentration (inhalable fraction)	2 mg/m <sup>3</sup>	PL OEL (2018-07-07)
2-butoxyethanol	111-76-2	TWALimit Value - eight hours	20 ppm 98 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STELShort term exposure limit	50 ppm 246 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
Further information: Identifies the possibility of significant uptake through the				

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version 2.6      Revision Date: 07.03.2024      Date of last issue: 07.03.2024      Print Date: 07.03.2024  
Date of first issue: 22.06.2016

	skin, Indicative			
		NDSMaximal Admissible Concentration	98 mg/m <sup>3</sup>	PL OEL (2018-07-07)
	Further information: Skin			
		NDSchMaximal Admissible Temporary Concentration	200 mg/m <sup>3</sup>	PL OEL (2018-07-07)
	Further information: Skin			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
pentane	Workers	Inhalation	Long-term systemic effects	3000 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	432 mg/kg
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	Workers	Inhalation	Acute systemic effects	1286,4 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	837,5 mg/m <sup>3</sup>
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Workers	Inhalation	Acute systemic effects	1286,4 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	837,5 mg/m <sup>3</sup>
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	Workers	Inhalation	Acute systemic effects	1286,4 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	837,5 mg/m <sup>3</sup>
2-butoxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	1091 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	89 mg/kg bw/day
	Workers	Inhalation	Acute local effects	246 mg/m <sup>3</sup>
calcium bis(dinonylnaphthalen esulphonate)	Workers	Inhalation	Long-term systemic effects	2,23 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	0,32 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version 2.6      Revision Date: 07.03.2024      Date of last issue: 07.03.2024      Print Date: 07.03.2024  
Date of first issue: 22.06.2016

Substance name	Environmental Compartment	Value
2-butoxyethanol	Fresh water	8,8 mg/l
	Marine water	0,88 mg/l
	Sewage treatment plant	463 mg/l
	Fresh water sediment	34,6 mg/kg
	Marine sediment	3,46 mg/kg
	Soil	2,33 mg/kg
	Intermittent use/release	26,4 mg/l
calcium bis(dinonylnaphthalenesulphonate)	Fresh water	0,27 mg/l
	Marine water	0,027 mg/l
	Intermittent use/release	2,7 mg/l
	Microbiological Activity in Sewage Treatment Systems	10 mg/l
	Fresh water sediment	4,69 mg/kg
	Marine sediment	0,469 mg/kg
	Soil	0,936 mg/kg

## 8.2 Exposure controls

### Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

### Personal protective equipment

Eye/face protection : Safety glasses with side-shields

#### Hand protection

Material : Nitrile rubber  
Break through time : > 10 min  
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.  
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.  
Short term only

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version 2.6	Revision Date: 07.03.2024	Date of last issue: 07.03.2024 Date of first issue: 22.06.2016	Print Date: 07.03.2024
----------------	------------------------------	---	---------------------------

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : yellow

Odour : characteristic

Odour Threshold : No data available

Melting point/range : No data available

Boiling point/boiling range : -161 °C (1.013 hPa)

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 9,4 %(V)

Lower explosion limit / Lower flammability limit : 0,6 %(V)

Flash point : 0 °C  
Method: Abel-Pensky

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable  
substance/mixture is non-soluble (in water)

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm<sup>2</sup>/s (40 °C)

Solubility(ies)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version 2.6	Revision Date: 07.03.2024	Date of last issue: 07.03.2024 Date of first issue: 22.06.2016	Print Date: 07.03.2024
----------------	------------------------------	---	---------------------------

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 8.327 hPa (20 °C)

Relative density : 0,638 (20 °C)  
Reference substance: Water  
The value is calculated

Density : 0,64 g/cm<sup>3</sup>  
(20 °C)

Bulk density : No data available

Relative vapour density : No data available

Particle characteristics  
Particle size : No data available

### 9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : No data available

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No hazards to be specially mentioned.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.  
Strong sunlight for prolonged periods.  
Risk of receptacle bursting.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:,  
Respiratory disorder, Dizziness, Drowsiness, Vomiting,  
Fatigue, Vertigo, Central nervous system depression

Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Method: Calculation method

Acute dermal toxicity : Symptoms: Redness, Local irritation

##### Components:

##### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

### Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg  
Method: OECD Test Guideline 402

### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

### isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: gas

### 2-butoxyethanol:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

LD50 (Guinea pig): 1.414 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l  
Test atmosphere: vapour  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

LC50: 3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The component/mixture is toxic after short term  
inhalation.

Acute dermal toxicity : LD50 (Guinea pig): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal  
toxicity

### calcium bis(dinonylnaphthalenesulphonate):

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 20.000 mg/kg

### butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

Test atmosphere: gas

### Skin corrosion/irritation

#### Product:

Remarks : Irritating to skin.

#### Components:

##### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Result : Repeated exposure may cause skin dryness or cracking.

##### **Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:**

Result : Repeated exposure may cause skin dryness or cracking.

##### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Result : Skin irritation

##### **Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Species : Rabbit  
Result : Skin irritation

##### **2-butoxyethanol:**

Species : Rabbit  
Assessment : Irritating to skin.  
Result : Irritating to skin.

##### **calcium bis(dinonylnaphthalenesulphonate):**

Species : Rabbit  
Assessment : Irritating to skin.  
Result : Irritating to skin.

### Serious eye damage/eye irritation

#### Product:

Remarks : Irritating to eyes.

#### Components:

##### **2-butoxyethanol:**

Species : Rabbit  
Assessment : Irritating to eyes.  
Result : Irritating to eyes.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

### calcium bis(dinonylnaphthalenesulphonate):

Species : Rabbit  
Assessment : Irritating to eyes.  
Result : Irritating to eyes.

### Respiratory or skin sensitisation

#### Product:

Remarks : This information is not available.

#### Components:

##### 2-butoxyethanol:

Test Type : Maximisation Test  
Species : Guinea pig  
Assessment : Did not cause sensitisation on laboratory animals.  
Result : Did not cause sensitisation on laboratory animals.

### calcium bis(dinonylnaphthalenesulphonate):

Species : Guinea pig  
Assessment : May cause sensitisation by skin contact.  
Result : May cause sensitisation by skin contact.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

#### Components:

##### 2-butoxyethanol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Rat  
Method: OECD Test Guideline 474  
Result: negative

Germ cell mutagenicity-  
Assessment : In vitro tests did not show mutagenic effects

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version 2.6	Revision Date: 07.03.2024	Date of last issue: 07.03.2024 Date of first issue: 22.06.2016	Print Date: 07.03.2024
----------------	------------------------------	---	---------------------------

### Carcinogenicity

#### Product:

Remarks : No data available

#### Components:

##### **2-butoxyethanol:**

Carcinogenicity - Assessment : Animal testing did not show any carcinogenic effects.

### Reproductive toxicity

#### Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

#### Components:

##### **2-butoxyethanol:**

Reproductive toxicity - Assessment : - Fertility -  
No toxicity to reproduction  
- Teratogenicity -  
Animal testing did not show any effects on foetal development.

##### **calcium bis(dinonylnaphthalenesulphonate):**

Reproductive toxicity - Assessment : - Fertility -  
No toxicity to reproduction

### STOT - single exposure

#### Product:

Remarks : No data available

#### Components:

##### **pentane:**

Assessment : May cause drowsiness or dizziness.

##### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Exposure routes : Inhalation  
Assessment : The substance or mixture is classified as specific target organ

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

toxicant, single exposure, category 3 with narcotic effects.

### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

### Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

### 2-butoxyethanol:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

### calcium bis(dinonylnaphthalenesulphonate):

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

### STOT - repeated exposure

#### Product:

Remarks : No data available

#### Components:

### 2-butoxyethanol:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

### calcium bis(dinonylnaphthalenesulphonate):

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

### Repeated dose toxicity

#### Product:

Remarks : This information is not available.

### Aspiration toxicity

#### Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version 2.6	Revision Date: 07.03.2024	Date of last issue: 07.03.2024 Date of first issue: 22.06.2016	Print Date: 07.03.2024
----------------	------------------------------	---	---------------------------

### Components:

#### **pentane:**

May be fatal if swallowed and enters airways.

#### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

May be fatal if swallowed and enters airways.

#### **Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:**

May be fatal if swallowed and enters airways.

#### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

May be fatal if swallowed and enters airways.

#### **Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

May be fatal if swallowed and enters airways.

#### **2-butoxyethanol:**

No aspiration toxicity classification

#### **calcium bis(dinonylnaphthalenesulphonate):**

No aspiration toxicity classification

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **Further information**

#### Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

### Components:

#### **Paraffin waxes and Hydrocarbon waxes:**

Remarks : Information given is based on data on the components and the toxicology of similar products.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

- Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available
- Toxicity to algae/aquatic plants : Remarks: No data available
- Toxicity to microorganisms : Remarks: No data available

#### Components:

##### **pentane:**

#### **Ecotoxicology Assessment**

- Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

##### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

#### **Ecotoxicology Assessment**

- Acute aquatic toxicity : Toxic to aquatic life.
- Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

##### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 48 h

##### **Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

#### **Ecotoxicology Assessment**

- Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

##### **2-butoxyethanol:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.474 mg/l  
Exposure time: 96 h  
Test Type: static test

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.550 mg/l  
Exposure time: 48 h  
Test Type: Immobilization  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 1.840 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 286 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 100 mg/l  
Exposure time: 21 d  
Species: Danio rerio (zebra fish)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 100 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: Reproduction Test  
Method: OECD Test Guideline 211

### calcium bis(dinonylnaphthalenesulphonate):

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 0,28 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0,27 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
Remarks: No toxicity at the limit of solubility

### Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

## 12.2 Persistence and degradability

### Product:

Biodegradability : Remarks: No data available

Physico-chemical : Remarks: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

removability

### Components:

#### **Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:**

Biodegradability : Result: Not readily biodegradable.

#### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Biodegradability : Result: Not rapidly biodegradable

#### **2-butoxyethanol:**

Biodegradability : Test Type: aerobic  
Result: rapidly biodegradable  
Biodegradation: 90 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

#### **calcium bis(dinonylnaphthalenesulphonate):**

Biodegradability : Result: Not readily biodegradable.

## 12.3 Bioaccumulative potential

### Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

### Components:

#### **Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:**

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : Remarks: No data available

#### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : log Pow: 4

#### **isobutane:**

Partition coefficient: n-octanol/water : log Pow: 2,88  
Method: OECD Test Guideline 107

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version 2.6	Revision Date: 07.03.2024	Date of last issue: 07.03.2024 Date of first issue: 22.06.2016	Print Date: 07.03.2024
----------------	------------------------------	---	---------------------------

### 2-butoxyethanol:

Bioaccumulation : Bioconcentration factor (BCF): 3,16

Partition coefficient: n-octanol/water : log Pow: 0,81 (25 °C)  
Method: OECD Test Guideline 107

### calcium bis(dinonylnaphthalenesulphonate):

Partition coefficient: n-octanol/water : log Pow: 10,96

### butane:

Partition coefficient: n-octanol/water : log Pow: 2,89  
Method: OECD Test Guideline 107

### propane:

Partition coefficient: n-octanol/water : log Pow: 2,36

## 12.4 Mobility in soil

### Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### Components:

#### calcium bis(dinonylnaphthalenesulphonate):

Assessment : Non-classified PBT substance. Non-classified vPvB substance

## 12.6 Endocrine disrupting properties

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : Toxic to aquatic life with long lasting effects.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.  
Offer empty spray cans to an established disposal company.  
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied  
16 05 04\*\*, gases in pressure containers (including halons)  
containing hazardous substances

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN : UN 1950

ADR : UN 1950

RID : UN 1950

IMDG : UN 1950

IATA : UN 1950

### 14.2 UN proper shipping name

ADN : AEROSOLS

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version 2.6	Revision Date: 07.03.2024	Date of last issue: 07.03.2024 Date of first issue: 22.06.2016	Print Date: 07.03.2024
----------------	------------------------------	---	---------------------------

**ADR** : AEROSOLS  
( )

**RID** : AEROSOLS

**IMDG** : AEROSOLS  
(naphtha (petroleum), hydrotreated light, cyclohexane)

**IATA** : Aerosols, flammable  
(naphtha (petroleum), hydrotreated light)

### 14.3 Transport hazard class(es)

**ADN** : 2

**ADR** : 2

**RID** : 2

**IMDG** : 2.1

**IATA** : 2.1

### 14.4 Packing group

**ADN**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

**RID**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

Packing group : Not assigned by regulation  
Labels : Flammable Gas

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : yes

#### ADR

Environmentally hazardous : yes

#### RID

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 75  
2-butoxyethanol (Number on list 3)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer (EC 1005/2009) : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP) : Not applicable

Regulation (EC) No 649/2012 of the European : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

Parliament and the Council concerning the export and import of dangerous chemicals (EU PIC)

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : Not applicable

P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

E2 ENVIRONMENTAL HAZARDS

18 Liquefied flammable gases (including LPG) and natural gas

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 93,32 %

### Other regulations:

Act of February 25, 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2020, item 2289)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Family, Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 with later amendments).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (consolidated text, Journal of Laws 2016 no. 0 item 1488)

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste (Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of February 15, 2021 on the entry into force of amendments to Annexes A and B to Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957 (Journal of Laws 202 poz.874 as amended)

Act of July 29, 2005 on drug addiction prevention (Journal of Laws of 2005, No. 179, item 1485, with later amendments)

Regulation (EU) 2016/425 of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

This information is not available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

### SECTION 16: Other information

#### Full text of H-Statements

EUH066 : Repeated exposure may cause skin dryness or cracking.  
H220 : Extremely flammable gas.  
H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H280 : Contains gas under pressure; may explode if heated.  
H302 : Harmful if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H331 : Toxic if inhaled.  
H336 : May cause drowsiness or dizziness.  
H411 : Toxic to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note P : The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

Note U (table 3.1) : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

2000/39/EC	:	2, Section 2.3.2.1, Note 2). Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	:	Europe. Indicative occupational exposure limit values
PL OEL	:	Poland. Occupational exposure limits for airborne toxic substances
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2006/15/EC / TWA	:	Limit Value - eight hours
PL OEL / NDS	:	Maximal Admissible Concentration
PL OEL / NDSch	:	Maximal Admissible Temporary Concentration

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315

#### Classification procedure:

Based on product data or assessment
Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL  
(Commission Regulation (EU) 2020/878)



## OKS 2101

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Based on product data or assessment
Aquatic Chronic 2	H411	Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.