

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : OKS 2351

Chemical nature : Active agent with propellant and solvent.

Manufacturer or supplier's details

Company name of supplier : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
D-82216 Maisach-Gernlinden
Tel.: +49 8142 3051 500
Fax.: +49 8142 3051 599
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com
Material Compliance Management

National contact :

Emergency telephone number : +86 532 8388 9090 (NRCC, only for hazardous chemicals)
+86 21 69225521

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant spray

Restrictions on use : Restricted to professional users.

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	: aerosol
Colour	: grey
Odour	: characteristic

Extremely flammable aerosol. Pressurised container: May burst if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

GHS Classification

Aerosols : Category 1

Skin irritation : Category 2

Specific target organ toxicity - single exposure : Category 3 (Narcotic effects)

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

Aspiration hazard : Category 1

Short-term (acute) aquatic hazard : Category 3

Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms :   

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing mist.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/containers according to the local government requirements.

Physical and chemical hazards

Extremely flammable aerosol. Pressurised container: May burst if heated.

Health hazards

Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Environmental hazards

Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Butane	106-97-8	>= 30 -< 50
propane	74-98-6	>= 10 -< 20
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	>= 10 -< 20
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	>= 10 -< 20
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 10 -< 20
Kaolin, calcined	92704-41-1	>= 1 -< 10
Aluminium powder (desensitized)	7429-90-5	>= 1 -< 10
Isobutane	75-28-5	>= 1 -< 10
n-hexane	110-54-3	>= 0.25 -< 1

4. FIRST AID MEASURES

If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

- Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
Wash off immediately with plenty of water.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.
- Most important symptoms and effects, both acute and delayed : Central nervous system depression
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.
Causes skin irritation.
Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema
Aspiration may cause pulmonary oedema and pneumonitis.
- Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : ABC powder
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

- Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Hazardous combustion products : Carbon oxides
Nitrogen oxides (NOx)
Metal oxides
- Specific extinguishing methods : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
Exposure to decomposition products may be a hazard to health.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.
- Prevention of secondary hazards : Only qualified personnel equipped with suitable protective equipment may intervene.

7. HANDLING AND STORAGE

Handling

- Advice on safe handling : Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
These safety instructions also apply to empty packaging which may still contain product residues.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Avoidance of contact : Oxidizing agents

Storage

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Store in accordance with the particular national regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Butane	106-97-8	STEL	1,000 ppm	ACGIH (2018-03-20)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH (2013-03-01)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH (2013-03-01)
Aluminium powder (desensitized)	7429-90-5	PC-TWA (Total dust)	3 mg/m ³ (Aluminium)	CN OEL (2019-08-27)
		TWA (Respirable)	1 mg/m ³ (Aluminium)	ACGIH (2013-03-01)

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

		particulate matter)		
Isobutane	75-28-5	STEL	1,000 ppm	ACGIH (2018-03-20)
n-hexane	110-54-3	PC-TWA	100 mg/m3	CN OEL (2019-08-27)
Further information: Skin				
		PC-STEL	180 mg/m3	CN OEL (2019-08-27)
Further information: Skin				
		TWA	50 ppm	ACGIH (2007-01-01)

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
n-hexane	110-54-3	2,5-hexanedione	Urine	After shift	4 mg/l	CN BEI (2019-08-27)
		2,5-hexanedione	Urine	After shift	35 micromol per litre	CN BEI (2019-08-27)
		2,5-Hexanedione	Urine	End of shift	0.5 mg/l	ACGIH BEI (2020-02-01)

Engineering measures : Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Short term only

Filter type : Filter type A-P

Eye/face protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hand protection

Material : butyl-rubber
Break through time : > 10 min
Protective index : Class 1

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

- Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.
- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : aerosol
- Colour : grey
- Odour : characteristic
- Odour Threshold : No data available
- pH : Not applicable
substance/mixture is non-soluble (in water)
- Melting point/range : No data available
- Boiling point/boiling range : -44.5 °C
(1,013 hPa)
- Flash point : -97.00 °C
Method: Abel-Pensky
- Evaporation rate : No data available
- Flammability (solid, gas) : Extremely flammable aerosol.
- Self-ignition : not auto-flammable
- Upper explosion limit / Upper flammability limit : 10.9 %(V)

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

Lower explosion limit / Lower flammability limit	:	0.8 %(V)
Vapour pressure	:	4,750 hPa (20 °C)
Relative vapour density	:	No data available
Relative density	:	0.7 (20 °C) Reference substance: Water The value is calculated
Density	:	0.70 g/cm ³ (20 °C)
Bulk density	:	No data available
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	< 20.5 mm ² /s (40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	No data available
Sublimation point	:	No data available
Metal corrosion rate	:	Not corrosive to metals

10. STABILITY AND REACTIVITY

Reactivity	:	No hazards to be specially mentioned.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No dangerous reaction known under conditions of normal use.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.
Risk of receptacle bursting.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:,
Respiratory disorder, Dizziness, Drowsiness, Vomiting,
Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

Butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402

Naphtha (petroleum), hydrotreated light:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 25.2 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

Kaolin, calcined:

Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

Aluminium powder (desensitized):

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

Acute inhalation toxicity : LC50 (Rat): > 5.09 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

n-hexane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 259.35 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 3,350 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Naphtha (petroleum), hydrotreated light:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.
GLP : yes

Kaolin, calcined:

Result : Repeated exposure may cause skin dryness or cracking.

Aluminium powder (desensitized):

Species : Rabbit
Assessment : No skin irritation
Result : No skin irritation

n-hexane:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit
Result : No eye irritation
Assessment : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit
Result : No eye irritation
Assessment : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

Naphtha (petroleum), hydrotreated light:

Species : Rabbit
Result : No eye irritation
Assessment : No eye irritation
Method : OECD Test Guideline 405
GLP : yes

Kaolin, calcined:

Result : Irritating to eyes.

Aluminium powder (desensitized):

Species : Rabbit
Result : No eye irritation
Assessment : No eye irritation

n-hexane:

Species : Rabbit
Result : No eye irritation
Assessment : No eye irritation
Method : OECD Test Guideline 405

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

Naphtha (petroleum), hydrotreated light:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

Aluminium powder (desensitized):

Species : Guinea pig
Assessment : Did not cause sensitisation on laboratory animals.
Result : Did not cause sensitisation on laboratory animals.

n-hexane:

Species : Mouse
Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Genotoxicity in vitro : Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

Genotoxicity in vivo : Species: Mouse
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Product:

Remarks : No data available

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Mouse
Application Route : Dermal
Method : OECD Test Guideline 451
Result : negative

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Effects on foetal development : Species: Rat
Application Route: Dermal
General Toxicity Maternal: NOAEL: 30 mg/kg body weight
Developmental Toxicity: NOAEL: 30 mg/kg body weight
Method: OECD Test Guideline 414

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

n-hexane:

Reproductive toxicity - Assessment : - Fertility -
Suspected human reproductive toxicant

STOT - single exposure

Components:

Naphtha (petroleum), hydrotreated light:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : May cause drowsiness or dizziness.

Kaolin, calcined:

Exposure routes : Inhalation
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

n-hexane:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Components:

n-hexane:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Repeated dose toxicity

Product:

Remarks : This information is not available.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

No aspiration toxicity classification

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

No aspiration toxicity classification

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

n-hexane:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Test Type: semi-static test
Method: OECD Test Guideline 211
GLP: yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test Type: static test

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d

Naphtha (petroleum), hydrotreated light:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 10 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l
Exposure time: 72 h
Test Type: static test

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Aluminium powder (desensitized):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.12 mg/l
Exposure time: 96 h
Test Type: static test
Remarks: No toxicity at the limit of solubility

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

n-hexane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 12.51 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 21.85 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 9.285 mg/l
Exposure time: 72 h

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : aerobic
Inoculum: activated sludge
Result: Not rapidly biodegradable
Biodegradation: 3 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
GLP: yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Biodegradability : aerobic
Inoculum: activated sludge
Result: Not rapidly biodegradable
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
GLP: yes

Naphtha (petroleum), hydrotreated light:

Biodegradability : aerobic
Inoculum: activated sludge
Result: rapidly biodegradable

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

Biodegradation: 90.35 %
Exposure time: 28 d

n-hexane:

Biodegradability : aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 21 %
Exposure time: 28 d
GLP: yes

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

Butane:

Partition coefficient: n-octanol/water : log Pow: 2.89
Method: OECD Test Guideline 107

propane:

Partition coefficient: n-octanol/water : log Pow: 2.36

Distillates (petroleum), hydrotreated heavy paraffinic:

Partition coefficient: n-octanol/water : log Pow: > 2

Naphtha (petroleum), hydrotreated light:

Partition coefficient: n-octanol/water : log Pow: 3.4 - 5.2

Isobutane:

Partition coefficient: n-octanol/water : log Pow: 2.88
Method: OECD Test Guideline 107

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

n-hexane:

Bioaccumulation : Bioconcentration factor (BCF): 501.19

Partition coefficient: n-octanol/water : log Pow: 4 (20 °C)
pH: 7

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

Other adverse effects

Product:

Additional ecological information : Harmful to aquatic life with long lasting effects.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Results of PBT and vPvB assessment : Non-classified vPvB substance Non-classified PBT substance

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Law on the Prevention and Control of Occupational Diseases

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals

Product name	Status	Reference number
OKS 2351	Listed	2828

List of ingredients	CAS-No.	Status	Reference number
Butane	106-97-8	Listed	2778
propane	74-98-6	Listed	139
Aluminium powder (desensitized)	7429-90-5	Listed	1377
Isobutane	75-28-5	Listed	2707
n-hexane	110-54-3	Listed	2789
Cyclohexane	110-82-7	Listed	953

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

Category Threshold quantity
Aerosols 150 t

Hazardous Chemicals for Priority Management under SAWS : Not applicable

Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not applicable

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import and Export : Not applicable

International Regulations

Montreal Protocol : Not applicable

Rotterdam Convention (Prior Informed Consent) : Not applicable

Stockholm Convention (Persistent Organic Pollutants) : Not applicable

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version 2.4 Revision Date: 2023-01-20 Date of last issue: 2021-09-08
Date of first issue: 2014-05-26 Print Date: 2023-01-20

The components of this product are reported in the following inventories:

IECSC : On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
CN BEI : China. Biological Occupational Exposure Indices
CN OEL : Occupational exposure limits for hazardous agents in the workplace - Chemical hazardous agents.

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
CN OEL / PC-TWA : Permissible concentration - time weighted average
CN OEL / PC-STEL : Permissible concentration - short term exposure limit

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods;

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519
CN



OKS 2351

Version	Revision Date:	Date of last issue: 2021-09-08
2.4	2023-01-20	Date of first issue: 2014-05-26 Print Date: 2023-01-20

vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.