

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2511

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Anticorrosion additive

Recommended restrictions : Restricted to professional users.
on use

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
D-82216 Maisach-Gernlinden
Tel.: +49 8142 3051 500
Fax.: +49 8142 3051 599
info@oks-germany.com

E-mail address of person : mcm@oks-germany.com
responsible for the SDS Material Compliance Management

National contact : EagleBurgmann Hungaria Kft.
Népfürdő utca 22
1138 Budapest
Hungary
Tel.: +36 1 814 8160
Fax: +36 1 319 8125
info.hu@eagleburgmann.com

1.4 Emergency telephone number

Emergency telephone num- : 0049 (0) 8142-3051-517
ber Egészségügyi Toxikológiai Tájékoztató Szolgálat (ETTSZ)
H-1096 Budapest, Nagyvárad tér 2.
Tel: +36 1 476 6464, +36 80 201 199

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)







OKS 2511

Version 2.6	Revision Date: 06.12.2022	Date of last issue: 19.04.2021 Date of first issue: 28.06.2016	Print Date: 06.12.2022
----------------	------------------------------	---	---------------------------

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - repeated exposure, Category 2, Auditory system	H373: May cause damage to organs through prolonged or repeated exposure if inhaled.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	   
Signal word	:	Danger
Hazard statements	:	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H315 Causes skin irritation. H319 Causes serious eye irritation. H373 May cause damage to organs (Auditory system) through prolonged or repeated exposure if inhaled. H410 Very toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P260 Do not breathe mist. P273 Avoid release to the environment. Storage: P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

reaction mass of ethylbenzene and xylene

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active agent with propellant and solvent.
Metal powder

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3 030-001-01-9 01-2119467174-37-XXXX	Aquatic Acute1; H400 Aquatic Chronic1; H410	M-Factor: 1/1	>= 25 - < 30
reaction mass of ethylbenzene and xylene	905-588-0 01-2119488216-32-XXXX	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319 STOT SE3; H335 STOT RE2; H373 Asp. Tox.1; H304	Note C	>= 10 - < 20
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21-	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1)	>= 10 - < 20

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version
2.6

Revision Date:
06.12.2022

Date of last issue: 19.04.2021
Date of first issue: 28.06.2016

Print Date:
06.12.2022

	XXXX			
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27-XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	$\geq 1 - < 10$
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29-XXXX	Flam. Liq.3; H226 STOT SE3; H336		$\geq 1 - < 10$
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	918-167-1 01-2119472146-39-XXXX	Flam. Liq.3; H226 Asp. Tox.1; H304; EUH066	Note P	$\geq 1 - < 10$
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29-XXXX	Flam. Liq.3; H226 STOT SE3; H336; EUH066		$\geq 1 - < 10$
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		$\geq 1 - < 10$
Substances with a workplace exposure limit :				
butane	106-97-8 203-448-7 601-004-00-0 01-2119474691-32-XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	$\geq 30 - < 50$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

- If inhaled : Obtain medical attention.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with soap and plenty of water.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
Seek medical advice.
- If swallowed : Move the victim to fresh air.
Keep respiratory tract clear.
Do NOT induce vomiting.
Obtain medical attention.
Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema
- Risks : Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : ABC powder
- Unsuitable extinguishing : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

media

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides
Metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Refer to protective measures listed in sections 7 and 8.
Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
These safety instructions also apply to empty packaging which may still contain product residues.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

7.3 Specific end use(s)

- Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
------------	---------	-------------------------------	--------------------	-------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version 2.6 Revision Date: 06.12.2022 Date of last issue: 19.04.2021 Print Date: 06.12.2022
Date of first issue: 28.06.2016

butane	106-97-8	TWA	2.350 mg/m3	HU OEL (2020-02-06)
	Further information: Irritants, simple suffocation gases, substances with minor health effects. No correction is required.			
		CEIL	9.400 mg/m3	HU OEL (2020-02-06)
	Further information: Irritants, simple suffocation gases, substances with minor health effects. No correction is required.			
reaction mass of ethylbenzene and xylene	Not Assigned	TWA	50 ppm 221 mg/m3	2000/39/EC (2000-06-16)
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m3	2000/39/EC (2000-06-16)
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		CEIL	442 mg/m3	HU OEL (2020-02-06)
	Further information: Substances which have a health hazard due to SHORT exposure. Corrected value = TWA x 8 / number of hours per day, Absorbed through the skin. The AC values take this property of the dangerous substances and the resulting exposure into consideration only in proportion to their permissible concentration in the air, Value disclosed in Directive 2000/39/EC			
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m3	2000/39/EC (2000-06-16)
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 550 mg/m3	2000/39/EC (2000-06-16)
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	275 mg/m3	HU OEL (2020-02-06)
	Further information: Irritants, simple suffocation gases, substances with minor health effects. No correction is required., Value disclosed in Directive 2000/39/EC			
		CEIL	550 mg/m3	HU OEL (2020-02-06)
	Further information: Irritants, simple suffocation gases, substances with minor health effects. No correction is required., Value disclosed in Directive 2000/39/EC			
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	Not Assigned	TWA (Mist)	5 mg/m3	HU OEL (2020-02-06)
	Further information: SCOEL/SUM/163/2011, Substances which have a health hazard after PROLONGED exposure. Corrected value = TWA x 40 / number of hours per week			
n-butyl acetate	123-86-4	TWA	241 mg/m3	HU OEL

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version 2.6 Revision Date: 06.12.2022 Date of last issue: 19.04.2021 Print Date: 06.12.2022
Date of first issue: 28.06.2016

				(2020-02-06)
	Further information: Irritants, simple suffocation gases, substances with minor health effects. No correction is required., Oversensitizing substance (it may cause illnesses detrimental to the skin, the respiratory system or other organs or groups of organs in persons with a propensity to oversensibility), Irritant substance (irritates the skin, the mucous membrane and the eyes or all three)			
		STEL	150 ppm 723 mg/m3	2019/1831/EU (2019-10-31)
	Further information: Indicative			
		TWA	50 ppm 241 mg/m3	2019/1831/EU (2019-10-31)
	Further information: Indicative			
		CEIL	723 mg/m3	HU OEL (2020-02-06)
	Further information: Irritants, simple suffocation gases, substances with minor health effects. No correction is required., Oversensitizing substance (it may cause illnesses detrimental to the skin, the respiratory system or other organs or groups of organs in persons with a propensity to oversensibility), Irritant substance (irritates the skin, the mucous membrane and the eyes or all three)			
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000/39/EC (2000-06-16)
	Further information: Indicative			
		TWA	1.210 mg/m3	HU OEL (2020-02-06)
	Further information: Irritants, simple suffocation gases, substances with minor health effects. No correction is required., Value disclosed in Directive 2000/39/EC, Irritant substance (irritates the skin, the mucous membrane and the eyes or all three)			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mass of ethylbenzene and xylene	Not Assigned	methyl-benzoyl glycines: 1500 mg/g Creatinine (Urine)	End of shift	HU BAT (2020-02-06)
		methyl-benzoyl glycines: 860 micromoles per millimole creatinine (Urine)	End of shift	HU BAT (2020-02-06)
acetone	67-64-1	Acetone: 80 mg/l (Urine)	End of shift	HU BAT (2020-02-06)
		Acetone: 1380 micromol per litre (Urine)	End of shift	HU BAT (2020-02-06)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version
2.6

Revision Date:
06.12.2022

Date of last issue: 19.04.2021
Date of first issue: 28.06.2016

Print Date:
06.12.2022

zinc powder — zinc dust (stabilised)	Workers	Inhalation	Long-term systemic effects	5 mg/m ³
	Workers	Skin contact	Long-term systemic effects	83 mg/kg
reaction mass of ethylbenzene and xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m ³
	Workers	Inhalation	Acute systemic effects	442 mg/m ³
	Workers	Inhalation	Long-term local effects	221 mg/m ³
	Workers	Inhalation	Acute local effects	442 mg/m ³
	Workers	Skin contact	Long-term systemic effects	212 mg/m ³
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m ³
	Workers	Inhalation	Long-term local effects	550 mg/m ³
	Workers	Skin contact	Long-term systemic effects	796 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m ³
	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Dermal	Long-term local effects	11 mg/cm ²
acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m ³
	Workers	Skin contact	Long-term systemic effects	186 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
zinc powder — zinc dust (stabilised)	Fresh water	0,0206 mg/l
	Fresh water sediment	235,6 mg/kg
	Marine water	0,0061 mg/l
	Marine sediment	121 mg/kg
	Microbiological Activity in Sewage Treatment Systems	0,052 mg/l
	Soil	106,8 mg/kg
reaction mass of ethylbenzene and xylene	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Sewage treatment plant	6,58 mg/l
	Fresh water sediment	12,46 mg/kg
	Marine sediment	12,46 mg/kg
	Soil	2,31 mg/kg
2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Marine water	0,0635 mg/l
	Intermittent use/release	6,35 mg/l
	Microbiological Activity in Sewage Treatment	100 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version 2.6 Revision Date: 06.12.2022 Date of last issue: 19.04.2021 Print Date: 06.12.2022
Date of first issue: 28.06.2016

	ment Systems	
	Fresh water sediment	3,29 mg/kg
	Marine sediment	0,329 mg/kg
	Soil	0,29 mg/kg
n-butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Microbiological Activity in Sewage Treatment Systems	35,6 mg/l
	Fresh water sediment	0,981 mg/kg
	Marine sediment	0,0981 mg/kg
	Soil	0,09 mg/kg
acetone	Fresh water	10,6 mg/l
	Marine water	1,06 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30,4 mg/kg
	Marine sediment	3,04 mg/kg
	Soil	29,5 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Recommended Filter type:
Organic gas and low boiling vapour type (AX)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version 2.6	Revision Date: 06.12.2022	Date of last issue: 19.04.2021 Date of first issue: 28.06.2016	Print Date: 06.12.2022
----------------	------------------------------	---	---------------------------

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : grey

Odour : characteristic

Odour Threshold : No data available

Melting point/range : No data available

Boiling point/boiling range : -41 °C (1.013 hPa)

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 10,9 %(V)

Lower explosion limit / Lower flammability limit : 1,1 %(V)

Flash point : -60,00 °C
Method: Abel-Pensky, closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : not determined

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version 2.6	Revision Date: 06.12.2022	Date of last issue: 19.04.2021 Date of first issue: 28.06.2016	Print Date: 06.12.2022
----------------	------------------------------	---	---------------------------

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 4.000 hPa (20 °C)

Relative density : 0,8 (20 °C)
Reference substance: Water
The value is calculated

Density : 0,80 g/cm³
(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : not auto-flammable

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.
Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Remarks: Harmful by inhalation.

Symptoms: Inhalation may provoke the following symptoms:,
Respiratory disorder

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Symptoms: Redness, Local irritation

Components:

zinc powder — zinc dust (stabilised):

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5,41 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity

reaction mass of ethylbenzene and xylene:

Acute oral toxicity : LD50 (Rat): 3.523 - 4.000 mg/kg

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

single contact with skin.

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 (Rat): 6.190 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): 35,7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402

n-butyl acetate:

Acute oral toxicity : LD50 (Rat): 10.768 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 17.600 mg/kg

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

zinc powder — zinc dust (stabilised):

Species : Rabbit
Assessment : No skin irritation
Result : No skin irritation

reaction mass of ethylbenzene and xylene:

Assessment : Irritating to skin.
Result : Irritating to skin.

2-methoxy-1-methylethyl acetate:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

n-butyl acetate:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : Repeated exposure may cause skin dryness or cracking.

acetone:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Product:

Remarks : Irritating to eyes.

Components:

zinc powder — zinc dust (stabilised):

Species : Rabbit
Exposure time : 24 h
Assessment : No eye irritation
Method : OECD Test Guideline 405

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

Result : No eye irritation
GLP : yes

reaction mass of ethylbenzene and xylene:

Assessment : Irritating to eyes.
Result : Irritating to eyes.

2-methoxy-1-methylethyl acetate:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

n-butyl acetate:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

acetone:

Species : Rabbit
Result : Eye irritation

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

zinc powder — zinc dust (stabilised):

Species : Guinea pig
Assessment : Did not cause sensitisation on laboratory animals.
Method : OECD Test Guideline 406
Result : Did not cause sensitisation on laboratory animals.
GLP : yes

reaction mass of ethylbenzene and xylene:

Assessment : Did not cause sensitisation on laboratory animals.
Result : Did not cause sensitisation on laboratory animals.

2-methoxy-1-methylethyl acetate:

Test Type : Maximisation Test
Species : Guinea pig

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

n-butyl acetate:

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available
Genotoxicity in vivo : Remarks: No data available

Components:

zinc powder — zinc dust (stabilised):

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

2-methoxy-1-methylethyl acetate:

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Animal testing did not show any mutagenic effects.

n-butyl acetate:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster cells
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Species: Mouse
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Animal testing did not show any mutagenic

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version 2.6	Revision Date: 06.12.2022	Date of last issue: 19.04.2021 Date of first issue: 28.06.2016	Print Date: 06.12.2022
----------------	------------------------------	---	---------------------------

effects.

Carcinogenicity

Product:

Remarks : No data available

Components:

zinc powder — zinc dust (stabilised):

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

2-methoxy-1-methylethyl acetate:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

n-butyl acetate:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

zinc powder — zinc dust (stabilised):

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction
- Teratogenicity -
No effects on or via lactation

reaction mass of ethylbenzene and xylene:

Reproductive toxicity - Assessment : - Fertility -
Animal testing did not show any effects on fertility.

2-methoxy-1-methylethyl acetate:

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction
- Teratogenicity -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

No toxicity to reproduction

n-butyl acetate:

Effects on fertility : Test Type: Two-generation study
Species: Rat
Application Route: inhalation (vapour)
General Toxicity - Parent: NOAEC: 750 mg/l
General Toxicity F1: NOAEC: 750 mg/l
General Toxicity F2: NOAEC: 750 mg/l
Method: OECD Test Guideline 416
Result: Embryotoxic effects and adverse effects on the offspring were detected.

Reproductive toxicity - Assessment : - Fertility -
No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.
- Teratogenicity -
No toxicity to reproduction

STOT - single exposure

Components:

reaction mass of ethylbenzene and xylene:

Exposure routes : Inhalation
Target Organs : Respiratory system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

2-methoxy-1-methylethyl acetate:

Exposure routes : Ingestion
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

n-butyl acetate:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

acetone:

Exposure routes : Inhalation
Assessment : May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

STOT - repeated exposure

Components:

reaction mass of ethylbenzene and xylene:

Exposure routes : Inhalation
Target Organs : Auditory system
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

2-methoxy-1-methylethyl acetate:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

n-butyl acetate:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Components:

n-butyl acetate:

Species : Rat
NOAEL : 125 mg/kg
Application Route : Oral

Aspiration toxicity

Product:

This information is not available.

Components:

zinc powder — zinc dust (stabilised):

No aspiration toxicity classification

reaction mass of ethylbenzene and xylene:

May be fatal if swallowed and enters airways.

2-methoxy-1-methylethyl acetate:

No aspiration toxicity classification

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

May be fatal if swallowed and enters airways.

n-butyl acetate:

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Risks of irreversible effects after a single exposure. Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance. Possible risk of irreversible effects.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: May cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

zinc powder — zinc dust (stabilised):

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 0,727 mg/l
Exposure time: 96 h
Test Type: static test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,937 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

reaction mass of ethylbenzene and xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

2-methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 373 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): >= 1.000 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : EC10 (activated sludge): > 1.000 mg/l
Exposure time: 0,5 h
Test Type: static test
Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: > 100 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: Reproduction Test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

Method: OECD Test Guideline 211

n-butyl acetate:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 44 mg/l
Exposure time: 48 h
Test Type: static test
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 397 mg/l
Exposure time: 72 h
Test Type: static test
- Toxicity to microorganisms : EC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h
Test Type: Growth inhibition
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: Reproduction Test
GLP: yes

12.2 Persistence and degradability

Product:

- Biodegradability : Remarks: No data available
- Physico-chemical removability : Remarks: No data available

Components:

reaction mass of ethylbenzene and xylene:

- Biodegradability : Result: rapidly biodegradable
Biodegradation: 90 %
Exposure time: 28 d

2-methoxy-1-methylethyl acetate:

- Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Biodegradability : Result: Not readily biodegradable.

n-butyl acetate:

Biodegradability : Test Type: Primary biodegradation
Result: rapidly biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

acetone:

Biodegradability : Result: rapidly biodegradable

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

reaction mass of ethylbenzene and xylene:

Partition coefficient: n-octanol/water : log Pow: 3,12 - 3,2

propane:

Partition coefficient: n-octanol/water : log Pow: 2,36

isobutane:

Partition coefficient: n-octanol/water : log Pow: 2,88
Method: OECD Test Guideline 107

2-methoxy-1-methylethyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 3,16

Partition coefficient: n-octanol/water : log Pow: 0,36 (25 °C)
Method: OECD Test Guideline 107
GLP: yes

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version 2.6	Revision Date: 06.12.2022	Date of last issue: 19.04.2021 Date of first issue: 28.06.2016	Print Date: 06.12.2022
----------------	------------------------------	---	---------------------------

n-butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)
pH: 7
Method: OECD Test Guideline 117
GLP: yes

acetone:

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 0,2

butane:

Partition coefficient: n-octanol/water : log Pow: 2,89
Method: OECD Test Guideline 107

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

2-methoxy-1-methylethyl acetate:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

n-butyl acetate:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version 2.6	Revision Date: 06.12.2022	Date of last issue: 19.04.2021 Date of first issue: 28.06.2016	Print Date: 06.12.2022
----------------	------------------------------	---	---------------------------

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied
16 05 04*, gases in pressure containers (including halons)
containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

IMDG : AEROSOLS
(zinc powder - zinc dust (stabilized))

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADN : 2

ADR : 2

RID : 2

IMDG : 2.1

IATA : 2.1

14.4 Packing group

ADN
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)
Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)
Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN
Environmentally hazardous : yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version 2.6	Revision Date: 06.12.2022	Date of last issue: 19.04.2021 Date of first issue: 28.06.2016	Print Date: 06.12.2022
----------------	------------------------------	---	---------------------------

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable
- REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
- REACH - List of substances subject to authorisation (Annex XIV) (EU. REACH-Annex XIV) : Not applicable
- Regulation (EC) No 1005/2009 on substances that deplete the ozone layer (EC 1005/2009) : Not applicable
- Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP) : Not applicable
- Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals (EU PIC) : Not applicable
- Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : Listed
- This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappear- acetone (ANNEX II)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

ances and thefts should be reported to the relevant national contact point. Please see https://ec.europa.eu/home-affairs/sites/homeaffairs/files/what-we-do/policies/crisis-and-terrorism/explosives/explosives-precursors/docs/list_of_competent_authorities_and_national_contact_points_en.pdf

: P2

P5c

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

E1 ENVIRONMENTAL HAZARDS

18 Liquefied extremely flammable gases (including LPG) and natural gas

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 73,38 %

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

2000 XXV. Law on chemical safety
44/2000. (XII 27) Ministry of health dangerous substances and preparations dangerous for certain procedures and arrangements for activities

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

EUH066 : Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

- H220 : Extremely flammable gas.
- H225 : Highly flammable liquid and vapour.
- H226 : Flammable liquid and vapour.
- H280 : Contains gas under pressure; may explode if heated.
- H304 : May be fatal if swallowed and enters airways.
- H312 : Harmful in contact with skin.
- H315 : Causes skin irritation.
- H319 : Causes serious eye irritation.
- H332 : Harmful if inhaled.
- H335 : May cause respiratory irritation.
- H336 : May cause drowsiness or dizziness.
- H373 : May cause damage to organs through prolonged or repeated exposure if inhaled.
- H400 : Very toxic to aquatic life.
- H410 : Very toxic to aquatic life with long lasting effects.
- EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

- Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Note P : The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.
- Note U (table 3.1) : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).
- 2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
- 2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
- HU BAT : Hungary. Permissible limit values of biological exposure (ef-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version	Revision Date:	Date of last issue: 19.04.2021	Print Date:
2.6	06.12.2022	Date of first issue: 28.06.2016	06.12.2022

HU OEL	: fect) indices Hungary. Occupational Exposure Limits - Annex 1: Permissible concentration values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
HU OEL / TWA	: Mean concentration
HU OEL / CEIL	: Peak concentration

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT RE 2	H373
Aquatic Acute 1	H400

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - HU
(Commission Regulation (EU) 2020/878)



OKS 2511

Version 2.6	Revision Date: 06.12.2022	Date of last issue: 19.04.2021 Date of first issue: 28.06.2016	Print Date: 06.12.2022
----------------	------------------------------	---	---------------------------

Aquatic Chronic 1

H410

Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.