according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : OKS 2551

Chemical nature : Active agent with propellant and solvent.

Metal powder

Manufacturer or supplier's details

Company name of supplier : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person responsible for the SDS

mcm@oks-germany.com

National contact

Emergency telephone number : +86 532 8388 9090 (NRCC, only for hazardous chemicals)

+86 21 69225521

Recommended use of the chemical and restrictions on use

Recommended use : Corrosion inhibitor

Restrictions on use : Restricted to professional users.

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: aerosolColour: grey

Odour : characteristic

Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long

lasting effects.

GHS Classification

Aerosols : Category 1

Skin irritation : Category 2

Eye irritation : Category 2A

according to GB/T 16483 and GB/T 17519 CN



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Specific target organ toxicity - :

single exposure

Category 3 (Narcotic effects)

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

Category 2

GHS label elements

Hazard pictograms







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing mist.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.



according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/containers according the local

government requirements.

Physical and chemical hazards

Extremely flammable aerosol. Pressurised container: May burst if heated.

Health hazards

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

Environmental hazards

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Dimethyl ether	115-10-6	>= 30 -< 50
butanone	78-93-3	>= 20 -< 30
Zinc (stabilized)	7440-66-6	>= 10 -< 20
Acetone	67-64-1	>= 10 -< 20
Cyclopentanone	120-92-3	>= 1 -< 10
n-Butyl acetate	123-86-4	>= 1 -< 2.5

4. FIRST AID MEASURES

If inhaled : Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.



according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Take off all contaminated clothing immediately.

Wash off immediately with soap and plenty of water. Get medical attention immediately if irritation develops and

orgists

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes. Seek medical advice.

If swallowed : Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Most important symptoms and effects, both acute and

delayed

Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Central nervous system depression

Causes skin irritation.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

Specific hazards during

firefighting

Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion

products

Carbon oxides

Halogenated compounds

according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Metal oxides

Specific extinguishing

methods

Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Exposure to decomposition products may be a hazard to

health.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition.

Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

Prevention of secondary

hazards

Only qualified personnel equipped with suitable protective

equipment may intervene.

7. HANDLING AND STORAGE

Handling

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces.



according to GB/T 16483 and GB/T 17519 CN



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or

burn, even after use.

Avoidance of contact : Oxidizing agents

Storage

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Store in accordance with the particular national regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butanone	78-93-3	PC-TWA	300 mg/m3	CN OEL (2019-08-27)
		PC-STEL	600 mg/m3	CN OEL (2019-08-27)
		TWA	200 ppm	ACGIH (2013-03-01)
		STEL	300 ppm	ACGIH (2013-03-01)
Acetone	67-64-1	PC-TWA	300 mg/m3	CN OEL (2019-08-27)
		PC-STEL	450 mg/m3	CN OEL (2019-08-27)
		TWA	250 ppm	ACGIH (2021-01-01)
		STEL	500 ppm	ACGIH (2021-01-01)
n-Butyl acetate	123-86-4	PC-TWA	200 mg/m3	CN OEL

according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

		(2019-08-27)
PC-STEL	300 mg/m3	CN OEL
		(2019-08-27)
TWA	50 ppm	ACGIH
		(2017-03-01)
STEL	150 ppm	ACGIH
		(2017-03-01)

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Samplin g time	Permissible concentratio n	Basis
butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI (2014-03- 01)
Acetone	67-64-1	Acetone	Urine	End of shift	50 mg/l	CN BEI (2019-08- 27)
		Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI (2017-03- 01)

Engineering measures : Use only in an area equipped with explosion proof exhaust

ventilation.

Handle only in a place equipped with local exhaust (or other

appropriate exhaust).

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Filter type A-P

Eye/face protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hand protection

Material : butyl-rubber



according to GB/T 16483 and GB/T 17519 CN



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Break through time : > 10 min Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol

Colour : grey

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : -42 °C

Method: Abel-Pensky

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Self-ignition : No data available

according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Upper explosion limit / Upper

flammability limit

26.2 %(V)

Lower explosion limit / Lower

flammability limit

1 %(V)

Vapour pressure : 3,700 hPa (20 °C)

Relative vapour density : No data available

Density : 0.92 g/cm3 (20 °C)

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20.5 mm2/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Risk of receptacle bursting.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Harmful by inhalation.

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute toxicity estimate: > 40 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

Dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 309 mg/l

Exposure time: 4 h Test atmosphere: gas



according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

butanone:

Acute oral toxicity : LD50 (Rat): 2,193 mg/kg

Method: OECD Test Guideline 423

GLP: yes

Acute inhalation toxicity : LC50 (Rat): 34 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Zinc (stabilized):

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : LC50 (Rat): > 5.41 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: yes

Assessment: The substance or mixture has no acute

inhalation toxicity

Acetone:

Acute oral toxicity : LD50 Oral (Rat): 5,800 mg/kg

Cyclopentanone:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): 10,768 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

according to GB/T 16483 and GB/T 17519 CN



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

GLP: yes

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 17,600 mg/kg

Skin corrosion/irritation

Product:

Result : Skin irritation

Remarks : Irritating to skin.

Components:

Dimethyl ether:

Assessment : No skin irritation Result : No skin irritation

butanone:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

Result : Repeated exposure may cause skin dryness or cracking.

Zinc (stabilized):

Species : Rabbit

Assessment : No skin irritation Result : No skin irritation

Cyclopentanone:

Species : Rabbit Result : Skin irritation

n-Butyl acetate:

Species : Rabbit

according to GB/T 16483 and GB/T 17519 CN



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Product:

Remarks : Irritating to eyes.

Components:

Dimethyl ether:

Result : No eye irritation Assessment : No eye irritation

butanone:

Species : Rabbit

Result : Irritating to eyes. Assessment : Irritating to eyes.

Method : OECD Test Guideline 405

Zinc (stabilized):

Species : Rabbit

Result : No eye irritation

Exposure time : 24 h

Assessment : No eye irritation

Method : OECD Test Guideline 405

GLP : yes

Acetone:

Species : Rabbit Result : Eye irritation

Cyclopentanone:

Species : Rabbit Result : Eye irritation

n-Butyl acetate:

Species : Rabbit

according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

GLP : yes

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Dimethyl ether:

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

butanone:

Test Type : Buehler Test Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

Zinc (stabilized):

Species : Guinea pig

Assessment : Did not cause sensitisation on laboratory animals.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

GLP : yes

n-Butyl acetate:

Test Type : Maximisation Test

Exposure routes : Dermal Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Dimethyl ether:

Genotoxicity in vitro : Test Type: Ames test

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Species: Drosophila melanogaster (vinegar fly)

Application Route: inhalation (gas) Method: OECD Test Guideline 477

Result: negative

butanone:

Germ cell mutagenicity -

Assessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

Zinc (stabilized):

Germ cell mutagenicity -

Assessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

n-Butyl acetate:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster cells Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Species: Mouse

Application Route: Oral

according to GB/T 16483 and GB/T 17519 CN



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity -

Assessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects., Animal testing did not show any mutagenic

effects.

Carcinogenicity

Product:

Remarks : No data available

Components:

Dimethyl ether:

Species : Rat

Application Route : inhalation (gas) Exposure time : 2 Years

: 47 mg/l

Method : OECD Test Guideline 453

Result : negative

butanone:

Carcinogenicity - : Not classifiable as a human carcinogen.

Assessment

Zinc (stabilized):

Carcinogenicity - : No evidence of carcinogenicity in animal studies.

Assessment

n-Butyl acetate:

Carcinogenicity - : Not classifiable as a human carcinogen.

Assessment

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development

: Remarks: No data available



according to GB/T 16483 and GB/T 17519 CN



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Components:

Dimethyl ether:

Reproductive toxicity -

Assessment

: - Fertility -

Animal testing did not show any effects on fertility.

butanone:

Reproductive toxicity -

Assessment

: - Fertility -

No toxicity to reproduction

- Teratogenicity -

No effects on or via lactation

Zinc (stabilized):

Reproductive toxicity -

Assessment

: - Fertility -

No toxicity to reproduction

- Teratogenicity -

No effects on or via lactation

n-Butyl acetate:

Effects on fertility : Test Type: Two-generation study

Species: Rat

Application Route: inhalation (vapour)
General Toxicity - Parent: NOAEC: 750 mg/l
General Toxicity F1: NOAEC: 750 mg/l
General Toxicity F2: NOAEC: 750 mg/l
Method: OECD Test Guideline 416

Result: Embryotoxic effects and adverse effects on the

offspring were detected.

Reproductive toxicity -

Assessment

: - Fertility -

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

- Teratogenicity -

No toxicity to reproduction

STOT - single exposure

Product:

Remarks : No data available

according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Components:

butanone:

Exposure routes : Inhalation

Target Organs : Respiratory system

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with narcotic effects.

May cause drowsiness or dizziness.

Acetone:

Exposure routes : Inhalation

Assessment : May cause drowsiness or dizziness.

n-Butyl acetate:

Exposure routes : Inhalation

Target Organs : Central nervous system

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Product:

Remarks : No data available

Components:

butanone:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

n-Butyl acetate:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

according to GB/T 16483 and GB/T 17519 CN



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Components:

n-Butyl acetate:

Species : Rat NOAEL : 125 mg/kg Application Route : Oral

Aspiration toxicity

Product:

This information is not available.

Components:

Dimethyl ether:

No aspiration toxicity classification

butanone:

No aspiration toxicity classification

Zinc (stabilized):

No aspiration toxicity classification

n-Butyl acetate:

No aspiration toxicity classification

Further information

Product:

Remarks : Risks of irreversible effects after a single exposure.

Ingestion causes irritation of upper respiratory system and

gastrointestinal disturbance.

according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Dimethyl ether:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4,100 mg/l

Exposure time: 96 h Test Type: semi-static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 4,400 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

EC50 (green algae): 154.9 mg/l

Exposure time: 96 h

butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 308 mg/l

Exposure time: 48 h Test Type: static test

according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 1,972

mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

GLP: yes

Toxicity to microorganisms : EC50 (Pseudomonas putida): 1,150 mg/l

Exposure time: 16 h Test Type: static test Method: DIN 38 412 Part 8

Zinc (stabilized):

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 0.727 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.937 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

M-Factor (Acute aquatic

toxicity)

: 1

M-Factor (Chronic aquatic

toxicity)

: 1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

n-Butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l

Exposure time: 96 h

Test Type: flow-through test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): 44 mg/l

Exposure time: 48 h

Test Type: static test



according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 397 mg/l

Exposure time: 72 h Test Type: static test

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 23 mg/l

Exposure time: 21 d

Test Type: Reproduction Test

GLP: yes

Toxicity to microorganisms : EC50 (Tetrahymena pyriformis): 356 mg/l

Exposure time: 40 h

Test Type: Growth inhibition

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical

removability

Remarks: No data available

Components:

Dimethyl ether:

Biodegradability : aerobic

Inoculum: activated sludge Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301D

butanone:

Biodegradability : aerobic

Inoculum: activated sludge Result: rapidly biodegradable Biodegradation: 98 %

Exposure time: 28 d

Method: OECD Test Guideline 301D

GLP: yes

according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Acetone:

Biodegradability : Result: rapidly biodegradable

Cyclopentanone:

Biodegradability : Result: rapidly biodegradable

n-Butyl acetate:

Biodegradability : Primary biodegradation

Result: rapidly biodegradable Biodegradation: 83 %

Exposure time: 28 d

Method: OECD Test Guideline 301D

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

Dimethyl ether:

Partition coefficient: n-

octanol/water

log Pow: 0.07 (25 °C)

butanone:

Bioaccumulation : Remarks: Due to the distribution coefficient n-octanol/water,

accumulation in organisms is not expected.

Partition coefficient: n-

octanol/water

log Pow: 0.3 (40 °C)

Method: OECD Test Guideline 117

GLP: yes

Acetone:

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n- : log Pow: 0.2

according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

octanol/water

Cyclopentanone:

Bioaccumulation : Remarks: No data available

n-Butyl acetate:

Partition coefficient: n- : log Pow: 2.3 (25 °C)

octanol/water pH: 7

Method: OECD Test Guideline 117

GLP: yes

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among : Remark

environmental compartments

Remarks: No data available

Other adverse effects

Product:

Additional ecological

information

Toxic to aquatic life with long lasting effects.

Components:

Dimethyl ether:

Results of PBT and vPvB

assessment

Non-classified vPvB substance Non-classified PBT substance

butanone:

Results of PBT and vPvB

assessment

Non-classified PBT substance Non-classified vPvB substance

n-Butyl acetate:

Results of PBT and vPvB

assessment

: Non-classified PBT substance Non-classified vPvB substance

according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1

IATA-DGR

UN/ID No. : UN 1950

Proper shipping name : Aerosols, flammable

Class : 2.1

Packing group : Not assigned by regulation

203

Labels : Flammable Gas

Packing instruction (cargo

aircraft)

Packing instruction : 203

(passenger aircraft)

IMDG-Code

UN number : UN 1950 Proper shipping name : AEROSOLS

(zinc powder - zinc dust (stabilized))

Class : 2.

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations



according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

GB 6944/12268

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Listed

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

No. / Code Chemical name / Category Threshold quantity

W3 Aerosols 150 t

Hazardous Chemicals for Priority Management under : Not applicable

SAWS

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals (2023) : Not applicable

International Regulations

Montreal Protocol : Not applicable

Rotterdam Convention (Prior Informed Consent) : Not applicable

Stockholm Convention (Persistent Organic Pollutants) : Not applicable

The components of this product are reported in the following inventories:

IECSC : Not in compliance with the inventory



according to GB/T 16483 and GB/T 17519 CN



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

16. OTHER INFORMATION

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
CN BEI : China. Biological Occupational Exposure Indices

CN OEL : Occupational exposure limits for hazardous agents in the

workplace - Chemical hazardous agents.

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

CN OEL / PC-TWA : Permissible concentration - time weighted average CN OEL / PC-STEL : Permissible concentration - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil: ASTM - American Society for the Testing of Materials: bw - Body weight: CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent. Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

according to GB/T 16483 and GB/T 17519



OKS 2551

Version Revision Date: Date of last issue: -

1.0 2024-03-07 Date of first issue: 2024-03-07 Print Date: 2024-03-07

Disclaimer

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.