

OKS 2611

Version	Revision Date:	Date of last issue: 29.11.2022	Print Date:
2.5	01.03.2023	Date of first issue: 13.06.2013	01.03.2023

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name : OKS 2611

Manufacturer or supplier's details

Company name of supplier : OKS Spezialechmierstoffe GmbH
Ganghoferstr. 47
D-82216 Maisach-Gernlinden
Tel.: +49 8142 3051 500
Fax.: +49 8142 3051 599
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com
Material Compliance Management

Emergency telephone number : +7 495 628 1687
+49 8142 3051 517

Recommended use of the chemical and restrictions on use

Recommended use : Cleaning agent / Cleaner
Detergent

Restrictions on use : Restricted to professional users.

2. HAZARDS IDENTIFICATION




GHS Classification (According to GOST 32423, GOST 32424 and GOST 32425)

Aerosols : Category 1
Skin irritation : Category 2
Eye irritation : Category 2A
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
Aspiration hazard : Category 1
Short-term (acute) aquatic hazard : Category 3
Long-term (chronic) aquatic hazard : Category 3

GHS-Labeling (According to GOST 31340)

OKS 2611

Version	Revision Date:	Date of last issue: 29.11.2022	Print Date:
2.5	01.03.2023	Date of first issue: 13.06.2013	01.03.2023

Hazard pictograms :   

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Other hazards which do not result in classification
None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical nature : Active substance with propellant
Solvent mixture

Components

Chemical name	Concentration (% w/w)	Occupational Exposure Limits		CAS-No.	EC-No.
		MAC value mg/m3 / TSEL value	Hazard Class		
propan-2-ol	>= 20 - < 30	MPC-TWA: 10 mg/m3 Data Source: RU OEL	3	67-63-0	200-661-7

OKS 2611

Version 2.5 Revision Date: 01.03.2023 Date of last issue: 29.11.2022 Print Date: 01.03.2023
Date of first issue: 13.06.2013

		MPC-STEL: 50 mg/m ³ Data Source: RU OEL	3		
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	>= 25 - < 30	No data available			927-241-2
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	>= 20 - < 25	No data available			921-024-6
acetone	>= 10 - < 20	MPC-TWA: 200 mg/m ³ Data Source: RU OEL	4	67-64-1	200-662-2
		MPC-STEL: 800 mg/m ³ Data Source: RU OEL	4		
carbon dioxide	>= 1 - < 10	MPC-TWA: 9.000 mg/m ³ Data Source: RU OEL	4	124-38-9	204-696-9
		MPC-STEL: 27.000 mg/m ³ Data Source: RU OEL	4		

4. FIRST AID MEASURES

- If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.

OKS 2611

Version	Revision Date:	Date of last issue: 29.11.2022	Print Date:
2.5	01.03.2023	Date of first issue: 13.06.2013	01.03.2023

- Thoroughly clean shoes before reuse.
Wash off immediately with plenty of water.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
Seek medical advice.
- If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.
- Most important symptoms and effects, both acute and delayed : Central nervous system depression
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.
Causes skin irritation.
Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema
Aspiration may cause pulmonary oedema and pneumonitis.
- Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Flammable properties

- Flash point : -18 °C
Method: Abel-Pensky
- Ignition temperature : No data available
- Upper explosion limit / Upper flammability limit : 13 %(V)
- Lower explosion limit / Lower flammability limit : 0,6 %(V)
- Flammability (solid, gas) : Extremely flammable aerosol.
- Suitable extinguishing media : ABC powder

OKS 2611

Version 2.5	Revision Date: 01.03.2023	Date of last issue: 29.11.2022 Date of first issue: 13.06.2013	Print Date: 01.03.2023
----------------	------------------------------	---	---------------------------

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Hazardous combustion products : Carbon oxides
- Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
Exposure to decomposition products may be a hazard to health.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
Only qualified personnel equipped with suitable protective equipment may intervene.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.

7. HANDLING AND STORAGE

- Advice on safe handling : Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.

OKS 2611

Version 2.5	Revision Date: 01.03.2023	Date of last issue: 29.11.2022 Date of first issue: 13.06.2013	Print Date: 01.03.2023
----------------	------------------------------	---	---------------------------

In case of insufficient ventilation, wear suitable respiratory equipment.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Keep away from fire, sparks and heated surfaces.
 Smoking, eating and drinking should be prohibited in the application area.
 Wash hands and face before breaks and immediately after handling the product.
 Do not get in eyes or mouth or on skin.
 Do not get on skin or clothing.
 Do not ingest.
 Do not use sparking tools.
 These safety instructions also apply to empty packaging which may still contain product residues.
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
 Store in accordance with the particular national regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Data Source
propan-2-ol	67-63-0	MPC-TWA (vapour and/or gas)	10 mg/m3	RU OEL (2021-02-03)
Further information: Class 3 - Moderately dangerous				
		MPC-STEL (vapour and/or gas)	50 mg/m3	RU OEL (2021-02-03)
Further information: Class 3 - Moderately dangerous				
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000/39/EC (2000-06-16)
		MPC-TWA (vapour and/or gas)	200 mg/m3	RU OEL (2021-02-03)
Further information: Class 4 - Low hazard				
		MPC-STEL (vapour and/or gas)	800 mg/m3	RU OEL (2021-02-03)
Further information: Class 4 - Low hazard				



OKS 2611

Version 2.5 Revision Date: 01.03.2023 Date of last issue: 29.11.2022 Print Date: 01.03.2023
Date of first issue: 13.06.2013

carbon dioxide	124-38-9	TWA	5.000 ppm 9.000 mg/m ³	2006/15/EC (2006-02-09)
		MPC-TWA (vapour and/or gas)	9.000 mg/m ³	RU OEL (2021-02-03)
Further information: Class 4 - Low hazard				
		MPC-STEL (vapour and/or gas)	27.000 mg/m ³	RU OEL (2021-02-03)
Further information: Class 4 - Low hazard				

Engineering measures : Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Recommended Filter type:
Organic gas and low boiling vapour type

Hand protection
Material : butyl-rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Eye protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

OKS 2611

Version 2.5	Revision Date: 01.03.2023	Date of last issue: 29.11.2022 Date of first issue: 13.06.2013	Print Date: 01.03.2023
----------------	------------------------------	---	---------------------------

Appearance : aerosol

Colour : colourless

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Melting point/range : No data available

Boiling point/boiling range : 56 °C
(1.013 hPa)

Flash point : -18 °C
Method: Abel-Pensky

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Self-ignition : not auto-flammable

Upper explosion limit / Upper flammability limit : 13 %(V)

Lower explosion limit / Lower flammability limit : 0,6 %(V)

Vapour pressure : 233 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0,7533 (20 °C)
Reference substance: Water
The value is calculated

Density : 0,75 g/cm³ (20 °C)

Bulk density : No data available

Solubility(ies)
Water solubility : insoluble

OKS 2611

Version 2.5	Revision Date: 01.03.2023	Date of last issue: 29.11.2022 Date of first issue: 13.06.2013	Print Date: 01.03.2023
----------------	------------------------------	---	---------------------------

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

 Viscosity, dynamic : No data available

 Viscosity, kinematic : < 20,5 mm²/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.
Risk of receptacle bursting.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

OKS 2611

Version	Revision Date:	Date of last issue: 29.11.2022	Print Date:
2.5	01.03.2023	Date of first issue: 13.06.2013	01.03.2023

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness. Harmful by inhalation.

Symptoms: Inhalation may provoke the following symptoms:,
Respiratory disorder, Dizziness, Drowsiness, Vomiting,
Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

propan-2-ol:

Acute oral toxicity : LD50 Oral (Rat): 5.840 mg/kg

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,8 g/kg
Assessment: The substance or mixture has no acute dermal toxicity

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

OKS 2611

Version	Revision Date:	Date of last issue: 29.11.2022	Print Date:
2.5	01.03.2023	Date of first issue: 13.06.2013	01.03.2023

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks : Irritating to eyes.

Components:

propan-2-ol:

Result : Irritating to eyes.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit
Result : No eye irritation
Assessment : No eye irritation

acetone:

Species : Rabbit
Result : Eye irritation

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

OKS 2611

Version	Revision Date:	Date of last issue: 29.11.2022	Print Date:
2.5	01.03.2023	Date of first issue: 13.06.2013	01.03.2023

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Test system: Rodent cell line
Method: OECD Test Guideline 473
Result: negative

Carcinogenicity

Product:

Remarks : No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

Components:

propan-2-ol:

Assessment : May cause drowsiness or dizziness.

OKS 2611

Version	Revision Date:	Date of last issue: 29.11.2022	Print Date:
2.5	01.03.2023	Date of first issue: 13.06.2013	01.03.2023

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Exposure routes : Inhalation
Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

acetone:

Exposure routes : Inhalation
Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Exposure routes : inhalation (vapour)
Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

May be fatal if swallowed and enters airways.

OKS 2611

Version	Revision Date:	Date of last issue: 29.11.2022	Print Date:
2.5	01.03.2023	Date of first issue: 13.06.2013	01.03.2023

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Risks of irreversible effects after a single exposure.
Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 22 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yes

OKS 2611

Version	Revision Date:	Date of last issue: 29.11.2022	Print Date:
2.5	01.03.2023	Date of first issue: 13.06.2013	01.03.2023

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EbC50 (Pseudokirchneriella subcapitata (green algae)): 26 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

propan-2-ol:

Biodegradability : Result: Readily biodegradable.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Biodegradability : Result: rapidly biodegradable

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

acetone:

Biodegradability : Result: rapidly biodegradable

OKS 2611

Version 2.5	Revision Date: 01.03.2023	Date of last issue: 29.11.2022 Date of first issue: 13.06.2013	Print Date: 01.03.2023
----------------	------------------------------	---	---------------------------

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

propan-2-ol:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 0,05

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : Remarks: No data available

acetone:

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 0,2

carbon dioxide:

Partition coefficient: n-octanol/water : log Pow: 0,83

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

Other adverse effects

Product:

Additional ecological information : Harmful to aquatic life with long lasting effects.

OKS 2611

Version 2.5	Revision Date: 01.03.2023	Date of last issue: 29.11.2022 Date of first issue: 13.06.2013	Print Date: 01.03.2023
----------------	------------------------------	---	---------------------------

Global warming potential

The Fifth Assessment Report of the United Nations Intergovernmental Panel on Climate Change (IPCC)

Components:

carbon dioxide:

20-year global warming potential: 1

100-year global warming potential: 1

Further information: No single lifetime can be given. The impulse response function for CO₂ from Joos et al. (2013) has been used. See also Supplementary Material Section 8.SM.11.

Hygienic standards:

(Allowable concentration in air, water, including fishery waters, soil)

Components	Air	Water	Soil	Data Source
propan-2-ol	Concentration that prevents irritation, reflex reactions, odors when exposed to 20-30 minutes - maximum one-time: 0,6 mg/m ³ Limiting health hazard indicator: reflectory Hazard class: Class 3 - moderately dangerous	Maximum Permissible Concentration: 0,01 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3 Maximum Permissible Concentration: 0,01 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 4 Maximum Allowable Concentration: 0,25 mg/l Limiting health hazard indicator: organoleptic; changes the smell of water Hazard class: Class 4 - low hazard	No data available	List 1 List 4 List 5
Hydrocarbons, C ₉ -C ₁₀ , n-alkanes,	No data available	Maximum Permissible Concentration:	No data available	List 5

OKS 2611

Version 2.5 Revision Date: 01.03.2023 Date of last issue: 29.11.2022 Print Date: 01.03.2023
Date of first issue: 13.06.2013

isoalkanes, cyclics, <2% aromatics		0,05 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3		
acetone	Concentration that prevents irritation, reflex reactions, odors when exposed to 20-30 minutes - maximum one-time: 0,35 mg/m ³ Limiting health hazard indicator: reflectory Hazard class: Class 4 - low hazard	Maximum Permissible Concentration: 0,05 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3 Maximum Allowable Concentration: 2,2 mg/l Limiting health hazard indicator: general sanitary Hazard class: Class 3 - moderately dangerous	No data available	List 1 List 4 List 5

For explanation of abbreviations see section 16.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied
16 05 04*, gases in pressure containers (including halons)
containing hazardous substances

OKS 2611

Version	Revision Date:	Date of last issue: 29.11.2022	Print Date:
2.5	01.03.2023	Date of first issue: 13.06.2013	01.03.2023

14. TRANSPORT INFORMATION

ADR

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2
Packing group : Not assigned by regulation
Labels : 2.1
Tunnel restriction code : (D)

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Federal Law of 21.07.1997 No. 116-FZ (amended on 11.06.2021) "On industrial safety of hazardous production facilities".
Federal Law of 24.06.1998 No. 89-FZ (amended on 02.07.2021) "On production and consumption waste".
Federal Law of 30.03.1999 No. 52-FZ (amended on 02.07.2021) "On the Sanitary and Epidemiological Well-Being of the Population" (amended and supplemented, entered into force on 31.10.2021).
Federal Law of 04.05.1999 No. 96-FZ "On the protection of atmospheric air" (as amended on December 8, 2020).

OKS 2611

Version	Revision Date:	Date of last issue: 29.11.2022	Print Date:
2.5	01.03.2023	Date of first issue: 13.06.2013	01.03.2023

Federal Law of 27.12.2002 No. 184-FZ (amended on 02.07.2021) "On Technical Regulation" (amended and supplemented, entered into force on 01.09.2021).
Federal Law of 10.01.2002 No. 7-FZ (amended on 02.07.2021) "On environmental protection".
Federal Law of 22.07.2008 No. 123-FZ "Technical Regulations on Fire Safety Requirements"
TECHNICAL REGULATIONS OF THE CUSTOMS UNION TR CU 030/2012 On requirements for lubricants, oils and special fluids (amended on 03.03.2017).

International Regulations

Montreal Protocol : Not applicable
Rotterdam Convention (Prior Informed Consent) : Not applicable
Stockholm Convention (Persistent Organic Pollutants) : Not applicable

16. OTHER INFORMATION

List of data sources used in the preparation of the Safety Data Sheet

GOST 30333-2007. Interstate standard. Safety data sheet for chemical products. Primary requirements.
GOST 12.1.004-91 System of labor safety standards (SSBT). Fire safety. General requirements.
GOST 12.1.007-76 Occupational safety standards system. Noxious substances. Classification and general safety requirements
GOST 12.1.044-89 SSBT. Fire and explosion hazard of substances and materials. Nomenclature of indicators and methods for their determination.
GOST 12.4.021 System of labor safety standards (SSBT). Ventilation systems. General requirements.
GOST 12.4.137-2001 Special footwear with leather uppers for protection against oil, oil products, acids, alkalis, non-toxic and explosive dust. Technical conditions.
GOST 12.4.252-2013 System of labor safety standards (SSBT). Means of individual protection of hands. Gloves. General technical requirements. Test methods.
GOST 14192-96. Interstate standard. Cargo marking. Minsk, 1998.
GOST 19433-88 Dangerous goods. Classification and labeling.
GOST 31340-2013. Interstate standard. Precautionary labeling of chemical products. General requirements.
GOST 32419-2013 Classification of the hazard of chemical products. General requirements.
GOST 32421-2013 Classification of chemical products, the hazard of which is due to physical and chemical properties. Test methods for explosive chemical products.
GOST 32423-2013 Hazard classification of mixed chemical products by their effects on the body.
GOST 32424-2013 Classification of the hazard of chemical products by their impact on the environment. Basic provisions.
GOST 32425-2013 Hazard classification of mixed chemical products in terms of environmental impact.
GOST R 53264-2019 Fire fighting equipment. Special protective clothing for firefighters. General technical requirements. Test methods.
GOST R 53265-2019 Fire fighting equipment. Personal protective equipment for the feet of the firefighter. General technical requirements. Test methods.

OKS 2611

Version	Revision Date:	Date of last issue: 29.11.2022	Print Date:
2.5	01.03.2023	Date of first issue: 13.06.2013	01.03.2023

GOST R 53268-2009 Fire fighting equipment. Fire rescue belts. General technical requirements. Test methods.
GOST R 53269-2019 Fire fighting equipment. Firefighters helmets. General technical requirements. Test methods.
SanPiN 1.2.2353-08 "Carcinogenic factors and basic requirements for the prevention of carcinogenic hazard".
SanPiN 1.2.3685-21 "Hygienic standards and requirements for ensuring the safety and (or) harmlessness to humans of environmental factors" dated 28.01.2021.
SanPiN 2.1.3684-21 "Sanitary and epidemiological requirements for the maintenance of the territories of urban and rural settlements, for water bodies, drinking water and drinking water supply, atmospheric air, soils, living quarters, the operation of industrial, public premises, the organization and implementation of sanitary and anti-epidemic (preventive) measures".
SanPiN 2.2.0.555-96. 2.2. Labor hygiene. Hygienic requirements for working conditions for women. Sanitary rules and regulations.
Carriage of dangerous goods, International maritime dangerous goods (IMDG) code.
Water quality standards for fishery water bodies, including standards for maximum permissible concentrations of harmful substances in the waters of fishery water bodies (approved by order of the Ministry of Agriculture of Russia dated December 13, 2016 No. 552).
Regulations for the carriage of dangerous goods (Appendix 1 and 2) to the Agreement on International Goods Transport by Rail (SMGS), 2009.
Agreement on International Goods Transport by Rail (SMGS).
UN Recommendations on the Transport of Dangerous Goods. Typical rules. Twenty-second revised edition. United Nations, New York and Geneva, 2021.
Montreal Protocol (Ozone Depleting Substances)
Stockholm Convention (Persistent Organic Pollutants)

Full text of other abbreviations

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Press. Gas	:	Gases under pressure
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	:	Europe. Indicative occupational exposure limit values
RU OEL	:	SanPiN 1.2.3685-21 Table 2.1, Table 2.8, Table 2.16 & Table 2.17 Maximum permissible concentrations (MPC) in the air of the working area
2000/39/EC / TWA	:	Limit Value - eight hours
2006/15/EC / TWA	:	Limit Value - eight hours
RU OEL / MPC-STEL	:	Maximum Permissible Concentration - Short Term Exposure
RU OEL / MPC-TWA	:	Maximum Permissible Concentration - Time Weighted Average
List 1	:	SanPiN 1.2.3685-21 Table 1.1, Table 1.10, & Table 1.11 Maximum permissible concentration (MPC) in the air of urban and rural settlements
List 4	:	SanPiN 1.2.3685-21 Table 3.13, Table 3.15, Table 3.16 & Table 3.17 Maximum permissible concentrations (MPC) of chemicals in the water of drinking systems of centralized, including hot, and non-centralized water supply, water of

OKS 2611

Version	Revision Date:	Date of last issue: 29.11.2022	Print Date:
2.5	01.03.2023	Date of first issue: 13.06.2013	01.03.2023

underground and surface water bodies of domestic drinking and cultural and domestic water use, water of swimming pools, water parks

List 5 : Order of the Russian Federal Fisheries Agency "Standards of maximum permissible concentrations of harmful substances in fishery water bodies"

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily



OKS 2611

Version	Revision Date:	Date of last issue: 29.11.2022	Print Date:
2.5	01.03.2023	Date of first issue: 13.06.2013	01.03.2023

mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.