

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : OKS 671

Chemical nature : Active substance with propellant  
Mineral oil.  
solid lubricant

#### Manufacturer or supplier's details

Company name of supplier : OKS Spezialschmierstoffe GmbH  
Ganghoferstr. 47  
D-82216 Maisach-Gernlinden  
Tel.: +49 8142 3051 500  
Fax.: +49 8142 3051 599  
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com  
Material Compliance Management

National contact :

Emergency telephone number : +86 532 8388 9090 (NRCC, only for hazardous chemicals)  
+86 21 69225521

#### Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : Restricted to professional users.

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

<b>Appearance</b>	: aerosol
<b>Colour</b>	: beige
<b>Odour</b>	: hydrocarbon-like

Extremely flammable aerosol. Pressurised container: May burst if heated. May be fatal if swallowed and enters airways. Causes mild skin irritation.

#### GHS Classification

Aerosols : Category 1

Skin irritation : Category 3

Aspiration hazard : Category 1

# SAFETY DATA SHEET



according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3    Revision Date: 2023-02-06    Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07    Print Date: 2023-02-07

### GHS label elements

Hazard pictograms	:	 
Signal word	:	Danger
Hazard statements	:	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters airways. H316 Causes mild skin irritation.
Precautionary statements	:	<b>Prevention:</b> P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. <b>Response:</b> P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P332 + P313 If skin irritation occurs: Get medical advice/ attention. <b>Storage:</b> P405 Store locked up. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. <b>Disposal:</b> P501 Dispose of contents/containers according the local government requirements.

### Physical and chemical hazards

Extremely flammable aerosol.Pressurised container: May burst if heated.

### Health hazards

Causes mild skin irritation. May be fatal if swallowed and enters airways.

### Environmental hazards

Not classified based on available information.

### Other hazards which do not result in classification

None known.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Butane	106-97-8	>= 30 -< 50
Naphtha (petroleum), hydrotreated heavy	64742-48-9	>= 30 -< 50
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	>= 1 -< 10
propane	74-98-6	>= 1 -< 10
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	>= 1 -< 10
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 1 -< 10
Isobutane	75-28-5	>= 1 -< 10
Sulfonic acids, petroleum, calcium salts	61789-86-4	>= 0.1 -< 1

## 4. FIRST AID MEASURES

- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
Seek medical advice.
- If swallowed : Move the victim to fresh air.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Obtain medical attention.  
Rinse mouth with water.  
Aspiration hazard if swallowed - can enter lungs and cause damage.
- Most important symptoms and effects, both acute and : Can be absorbed through skin.  
Risk of product entering the lungs on vomiting after ingestion.

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

delayed      Health injuries may be delayed.  
Inhalation may provoke the following symptoms:  
Unconsciousness  
Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness  
Skin contact may provoke the following symptoms:  
Erythema  
Aspiration may cause pulmonary oedema and pneumonitis.

Notes to physician      :      Treat symptomatically.

## 5. FIREFIGHTING MEASURES

Suitable extinguishing media      :      ABC powder

Unsuitable extinguishing media      :      High volume water jet

Specific hazards during firefighting      :      Fire Hazard  
Do not let product enter drains.  
Contains gas under pressure; may explode if heated.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products      :      Carbon oxides

Specific extinguishing methods      :      Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Cool containers/tanks with water spray.

Special protective equipment for firefighters      :      In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.  
Exposure to decomposition products may be a hazard to health.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures      :      Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Do not breathe vapours or spray mist.  
Refer to protective measures listed in sections 7 and 8.

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

- Environmental precautions : Try to prevent the material from entering drains or water courses.  
Prevent further leakage or spillage if safe to do so.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.  
Non-sparking tools should be used.
- Prevention of secondary hazards : Only qualified personnel equipped with suitable protective equipment may intervene.

## 7. HANDLING AND STORAGE

### Handling

- Advice on safe handling : Do not use in areas without adequate ventilation.  
Do not breathe vapours or spray mist.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Keep away from fire, sparks and heated surfaces.  
Smoking, eating and drinking should be prohibited in the application area.  
Wash hands and face before breaks and immediately after handling the product.  
Do not get in eyes or mouth or on skin.  
Do not get on skin or clothing.  
Do not ingest.  
Do not use sparking tools.  
These safety instructions also apply to empty packaging which may still contain product residues.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

- Avoidance of contact : Oxidizing agents

### Storage

- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
Store in accordance with the particular national regulations.

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Butane	106-97-8	STEL	1,000 ppm	ACGIH (2018-03-20)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH (2013-03-01)
Distillates (petroleum), solvent- dewaxed heavy paraffinic	64742-65-0	TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH (2013-03-01)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH (2013-03-01)
Isobutane	75-28-5	STEL	1,000 ppm	ACGIH (2018-03-20)

**Engineering measures** : Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.  
Short term only

Filter type : Filter type A-P

Eye/face protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

#### Hand protection

Material : Nitrile rubber  
Break through time : > 10 min  
Protective index : Class 1

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

- Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.
- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : aerosol
- Colour : beige
- Odour : hydrocarbon-like
- Odour Threshold : No data available
- pH : Not applicable  
substance/mixture is non-soluble (in water)
- Melting point/range : No data available
- Boiling point/boiling range : -44 °C  
(1,013 hPa)
- Flash point : -97 °C  
Method: Abel-Pensky, closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : Extremely flammable aerosol.
- Self-ignition : No data available
- Upper explosion limit / Upper flammability limit : 8.5 %(V)

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

Lower explosion limit / Lower flammability limit	:	0.6 %(V)
Vapour pressure	:	5,500 hPa (20 °C)
Relative vapour density	:	No data available
Relative density	:	0.67 (20 °C) Reference substance: Water The value is calculated
Density	:	0.67 g/cm <sup>3</sup> (20 °C)
Bulk density	:	No data available
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	< 20.5 mm <sup>2</sup> /s ( 40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	No data available
Sublimation point	:	No data available
Metal corrosion rate	:	Not corrosive to metals

## 10. STABILITY AND REACTIVITY

Reactivity	:	No hazards to be specially mentioned.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No dangerous reaction known under conditions of normal use.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

Conditions to avoid : Heat, flames and sparks.  
Strong sunlight for prolonged periods.  
Risk of receptacle bursting.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No decomposition if stored and applied as directed.

## 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

#### Product:

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Symptoms: Inhalation may provoke the following symptoms:,  
Respiratory disorder

Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may  
cause defatting resulting in drying, redness and possible  
blistering.

Symptoms: Skin disorders

#### Components:

##### **Butane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: gas

##### **Naphtha (petroleum), hydrotreated heavy:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402

##### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402

### **Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402

### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: yes  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

### **Isobutane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: gas

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

---

### Skin corrosion/irritation

#### Product:

Remarks : This information is not available.

#### Components:

##### **Naphtha (petroleum), hydrotreated heavy:**

Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : Mild skin irritation

Result : Repeated exposure may cause skin dryness or cracking.

##### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

##### **Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

##### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : No skin irritation

### Serious eye damage/eye irritation

#### Product:

Remarks : Contact with eyes may cause irritation.

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

### Components:

#### **Naphtha (petroleum), hydrotreated heavy:**

Species : Rabbit  
Result : No eye irritation  
Assessment : No eye irritation  
Method : OECD Test Guideline 405

#### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Rabbit  
Result : No eye irritation  
Assessment : No eye irritation  
Method : OECD Test Guideline 405  
GLP : yes

#### **Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Species : Rabbit  
Result : No eye irritation  
Assessment : No eye irritation  
Method : OECD Test Guideline 405  
GLP : yes

#### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rabbit  
Result : No eye irritation  
Assessment : No eye irritation  
Method : OECD Test Guideline 405  
GLP : yes

### **Respiratory or skin sensitisation**

#### Product:

Remarks : This information is not available.

### Components:

#### **Naphtha (petroleum), hydrotreated heavy:**

Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

### Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.  
GLP : yes

### Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.  
GLP : yes

### Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

### Sulfonic acids, petroleum, calcium salts:

Assessment : The product is a skin sensitizer, sub-category 1B.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

#### Components:

### Naphtha (petroleum), hydrotreated heavy:

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

### Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Genotoxicity in vitro : Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

Result: negative

Genotoxicity in vivo : Species: Mouse  
Application Route: Oral  
Method: OECD Test Guideline 474  
Result: negative

### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Test system: Chinese hamster ovary cells  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 473  
Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test  
Species: Mouse  
Cell type: Bone marrow  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

### **Carcinogenicity**

#### **Product:**

Remarks : No data available

#### **Components:**

##### **Naphtha (petroleum), hydrotreated heavy:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

##### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

##### **Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Species : Mouse  
Application Route : Dermal

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

Method : OECD Test Guideline 451  
Result : negative

### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

### **Reproductive toxicity**

#### **Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

#### **Components:**

### **Naphtha (petroleum), hydrotreated heavy:**

Reproductive toxicity - Assessment : - Fertility -  
No toxicity to reproduction  
- Teratogenicity -  
No toxicity to reproduction

### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Reproductive toxicity - Assessment : - Fertility -  
No toxicity to reproduction

### **Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Effects on foetal development : Species: Rat  
Application Route: Dermal  
General Toxicity Maternal: NOAEL: 30 mg/kg body weight  
Developmental Toxicity: NOAEL: 30 mg/kg body weight  
Method: OECD Test Guideline 414

### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Effects on foetal development : Species: Rat  
Application Route: Dermal  
General Toxicity Maternal: LOAEL: 125 mg/kg body weight  
Teratogenicity: NOAEL:  $\geq 2,000$  mg/kg body weight  
Developmental Toxicity: NOAEL:  $\geq 2,000$  mg/kg body weight  
Embryo-foetal toxicity: NOAEL:  $\geq 2,000$  mg/kg body weight

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

---

Method: OECD Test Guideline 414  
Result: No effects on fertility and early embryonic development were detected.

Reproductive toxicity - Assessment : - Fertility -  
No toxicity to reproduction  
- Teratogenicity -  
No toxicity to reproduction

### STOT - single exposure

#### Components:

##### **Naphtha (petroleum), hydrotreated heavy:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

##### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

### STOT - repeated exposure

#### Components:

##### **Naphtha (petroleum), hydrotreated heavy:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

##### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

### Repeated dose toxicity

#### Product:

Remarks : This information is not available.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

### Aspiration toxicity

**Product:**

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

**Components:**

**Naphtha (petroleum), hydrotreated heavy:**

May be fatal if swallowed and enters airways.

**Distillates (petroleum), hydrotreated heavy paraffinic:**

No aspiration toxicity classification

**Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

No aspiration toxicity classification

**Distillates (petroleum), hydrotreated heavy naphthenic:**

No aspiration toxicity classification

### Further information

**Product:**

Remarks : Information given is based on data on the components and the toxicology of similar products.

---

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

**Product:**

Toxicity to fish :  
Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates :  
Remarks: No data available

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

### Components:

#### **Naphtha (petroleum), hydrotreated heavy:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h

#### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: Immobilization  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 21 d  
Test Type: semi-static test  
Method: OECD Test Guideline 211  
GLP: yes

#### **Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 21 d

### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : LC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)):  $\geq$  1,000 mg/l  
Exposure time: 28 d  
Remarks: The value is calculated

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 21 d  
Test Type: Reproduction Test  
Method: OECD Test Guideline 211

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

### Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

Physico-chemical  
removability : Remarks: No data available

#### Components:

##### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Biodegradability : aerobic  
Inoculum: activated sludge  
Result: Not rapidly biodegradable  
Biodegradation: 3 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B  
GLP: yes

##### **Distillates (petroleum), solvent-dewaxed heavy paraffinic:**

Biodegradability : aerobic  
Inoculum: activated sludge  
Result: Not rapidly biodegradable  
Biodegradation: 31 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B  
GLP: yes

##### **Distillates (petroleum), hydrotreated heavy naphthenic:**

Biodegradability : aerobic  
Inoculum: activated sludge  
Result: Not rapidly biodegradable  
Biodegradation: 3 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B  
GLP: yes

### Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

### Components:

#### **Butane:**

Partition coefficient: n-octanol/water : log Pow: 2.89  
Method: OECD Test Guideline 107

#### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Partition coefficient: n-octanol/water : log Pow: > 2

#### **propane:**

Partition coefficient: n-octanol/water : log Pow: 2.36

#### **Isobutane:**

Partition coefficient: n-octanol/water : log Pow: 2.88  
Method: OECD Test Guideline 107

### **Mobility in soil**

#### Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

### **Other adverse effects**

#### Product:

Additional ecological information : No information on ecology is available.

### Components:

#### **Naphtha (petroleum), hydrotreated heavy:**

Results of PBT and vPvB assessment : Non-classified PBT substance Non-classified vPvB substance

#### **Distillates (petroleum), hydrotreated heavy paraffinic:**

Results of PBT and vPvB assessment : Non-classified vPvB substance Non-classified PBT substance

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

### Distillates (petroleum), hydrotreated heavy naphthenic:

Results of PBT and vPvB assessment : Non-classified PBT substance Non-classified vPvB substance

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

- Waste from residues : Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and national regulations.
- Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.  
Offer empty spray cans to an established disposal company.  
Pressurized container: Do not pierce or burn, even after use.

## 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1

#### IATA-DGR

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

#### IMDG-Code

UN number : UN 1950  
Proper shipping name : AEROSOLS

Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### GB 6944/12268

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 15. REGULATORY INFORMATION

### National regulatory information

#### Law on the Prevention and Control of Occupational Diseases

### Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals

Product name	Status	Reference number
OKS 671	Listed	2828

List of ingredients	CAS-No.	Status	Reference number
Butane	106-97-8	Listed	2778
propane	74-98-6	Listed	139
Isobutane	75-28-5	Listed	2707

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

Category      Threshold quantity  
Aerosols      150 t

Hazardous Chemicals for Priority Management under SAWS : Not applicable

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

### Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not applicable

### Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import and Export : Not applicable

### International Regulations

Montreal Protocol : Not applicable

Rotterdam Convention (Prior Informed Consent) : Not applicable

Stockholm Convention (Persistent Organic Pollutants) : Not applicable

### The components of this product are reported in the following inventories:

IECSC : On the inventory, or in compliance with the inventory

## 16. OTHER INFORMATION

Date format : yyyy/mm/dd

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 671

Version 4.3      Revision Date: 2023-02-06      Date of last issue: 2021-09-06  
Date of first issue: 2014-05-07      Print Date: 2023-02-07

---

Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

### Disclaimer

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.